









## ●● Specification

|                       |   |   |   |   |  |   |
|-----------------------|---|---|---|---|--|---|
| Power supply voltage  | 24 V d.c  |   | 110 V, 125 V d.c  |   | 110 V a.c, 220 V a.c   |   |
| Input type            | Without voltage dropping type   |   | Resistance-voltage dropping type  |   | Condenser voltage dropping type  |   |
| Type                  | CD-SA   | CD-RA   | CD-SB   | CD-RB   | CD-SC, SD  | CD-RC, RD   |
| Appearance            |  |  |  |  |  |  |
| LED rated voltage     | 24 V d.c  |   |   |   |  |   |
| LED base              | Exclusive unit  |   |   |   |  |   |
| LED color             | red, green, yellow, white, orange and blue  |   |   |   |  |   |
| Insulation resistance | Min 100 M $\Omega$  |   |   |   |  |   |
| Dielectric voltage    | 2,000 V a.c (for one minute)  |   |   |   |  |   |
| Power consumption     | 0.68 W (24 V d.c, 20 mA)  |   |   |   |  |   |
| Life expectancy       | 50,000 hours (24 V d.c, 25 °C)  |   |   |   |  |   |
| Ambient temperature   | -20 °C ~ 40 °C  |   |   |   |  |   |
| Ambient humidity      | -25 °C ~ 55 °C  |   |   |   |  |   |
| Storage temperature   | 45 ~ 85 % R.H   |   |   |   |  |   |
| Weight                | About 65 g  | About 80 g  | About 75 g  | About 90 g  | About 80 g   | About 93 g  |