

TIMER

PROGRAMMABLE TIMER

Universal Range



MODEL	UTR-1044	UTR-2044	UTR-444	UTR-413
Dimension (HxWxD) mm	96 X 96 X 50	72 X 72 X 85	48 X 48 X 95	48 X 48 X 95
Panel Cutout (mm)	92 X 92	68 X 68	44X 44	44X 44
Display	Upper : 7 segment, 4 digit, 0.56" RED LED - Time Lower : 7 segment, 4 digit, 0.4" GREEN LED - Set Time		Upper : 7 segment, 4 digit, 0.4" RED LED - Time Lower : 7 segment, 4 digit, 0.3" GREEN LED - Set Time	Single : 7 segment, 3 digit, 0.56" RED LED
INPUT	Micro switch / Limit switch / Proximity Power ON / Enable / Trigger			Micro Switch/Limit Switch
Start Pulse				
Start PulseType				
OUTPUT	1 - Relay			
Control Output	2 C/O, 5A, 230V AC			
Relay Ratings	12V DC approximately (Optional)			
SSR / Buzzer				
SPECIFICATION	1 - Set Point - (Delayed ON / Instant ON) (Configurable) 2 - Set Point - (Cycle Mode)			1 - Set Point
Set point				
Operating Mode	Delayed ON / Instant ON / Cycle Mode(Configurable)			
Reset Facility	Front & Back Both Reset Available			
Time Setting Range	99.99 / 999.9 / 9999 sec (Configurable)		9.99 / 99.9 / 999 sec	
	99.59 min/sec, 999.9 min, 9999 min (Configurable) 999.9 hrs, 9999 for hrs, 99.59 hrs/min (Configurable)		9.59 min/sec, 99.9 min, 999 min 99.9 hrs, 999 for hrs, 9.59 hrs/min	
Counting direction	Up / Down (Configurable)			
Memory retention	Yes / No (Configurable)			
Parameter lock	ON / OFF (Configurable)			
Power Supply	90-270V AC/DC, 50/60 Hz, SMPS			
Indication	LED for Relay Status Indication			
Enclosure Material	Plastic			
Operating Ambient Temp	0°C - 55°C			
Relative Humidity	Upto 95% RH Non Condensing			